# TUCANO BLOW GUN WITH SCRATCHPROOF SAFETY NOZZLE

AIRSET® TUCANO

**Cod. TCN PS 4040**

With rubber tip. Protects surfaces from scratches. Nozzle is designed for sensitive operations, like car cleaning or drying delicate parts; where it's important to preserve the surface. Blowgun is also compact and quiet. Nozzle offers a wide flow for cleaning surfaces, objects and machinery. The vented tip also prevents pressure exceeding 30 PSI (2 Bar) if the tip becomes blocked (conforms with OSHA Std 1-13.1).

**Variable airflow trigger**

Tucano adopts a special valve which allows a progressive control of the lever: this reduces the noise level and air consumption. In the progressive mode the operator can adjust the flow with great precision, which is useful in the most jobs. Instead, fully pressing the lever will use all the blowing force

**Ergonomic handle**

Tucano offers a Soft-Touch handle, made of soft ergonomic rubber, for comfort and easy handling. This material reduces the risk of repetitive strain injuries

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

| | |
|---|---|
| Blowing force (with a 6bar - 90psi inlet) | **2,3 N** |
| Air consumption (with a 6bar - 90psi inlet) | **275 l/m - 9.7 scfm** |
| Sound level (with a 6bar - 90psi inlet) | **80 dB(A)** |
| Connection | **1/4" BSP** |
| Weight | **136 g - 0.30 lbs** |
| Working temperature | **-10°/70° - 14/158 °F** |
| Max. Pressure | **16 Bar - 235 psi** |
| Nozzle length | **66 mm - 2.6"** |

MATERIALS

| | |
|---|---|
| Handle | **Nylon and rubber** |
| Connection | **Brass** |
| Valve | **Acetal and stainless steel** |
| Body | **Nylon** |
| Nozzle | **Nylon and rubber** |

VERSIONS

| Code | Description | Connection |
|---|---|---|
| TCN PS 4040 | Airset Tucano Blow Anti-Scratch BSP | 1/4" BSP |
| TCN PS 4041 | Airset Tucano Blow Anti-Scratch NPT | 1/4" NPT |

REGULATIONS

| |
|---|
| **EU 2003/10/CE** Max. 85 dB |
| **OSHA 1910.95 (b)** Max. 90 dB 8h |
| **OSHA STD 1-13.1** Max. 2 bar / 30 psi if the tip becomes blocked |
| **SUVA PRO** |

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.