AL 100 Turbine digital flow meter - For Diesel



CARBUSET

Cod. ALD10010

AL 100 is a digital turbine meter for displaying the flow of Diesel. It can be installed on a pump, system, line or at the end of the delivery hose. For example: before the dispensing gun of a re-fuel station.

Thanks to its body, made of technopolymer and gum covered, AL 100 it’s suitable for any kind of working environment. **Electronics are sealed** to prevent malfunctioning caused by dust or liquid infiltration.

Easy to install, with a 4 positions Swivel screen.

Handy and safe: **batteries change it’s made without access to the electronics.** Powered from 2 batteries AAA 1,5 V

Adpter F/F 1” included

Functions

- Work function: shows together Partial 5 digits, from 0,01 to 9.999 and Total, 5 digits, from 0,1 to 99.999 resettable
- Total, resettable, 9 digits, from 0,1 to 999.999.999
- Total, non-resettable, 9 digits, from 0,1 to 999.999.999
- Flow rate, up to 100 l/m
- Units available: Liters (l), Gallons (G), Quarts (qt) e Pints (pt)
- Calibration: to ensure maximum precision
- Low battery warning

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

Connection	**M/M 1” BSP**
Working temperature	**-10° + 40°/14 °F to 104 °F**
Liquid temperature	**-10° + 35°/14 °F to 95°F**
Min. Flow rate	**15 l/m/3,96 gpm**
Max. flow rate	**100 l/m/26,42 gpm**
Max. pressure	**20 bar/290 psi**
Dimension	**118x59x82 mm/4,64x2,32x3,22 in**
Power	**2x 1,5 V AAA**

MATERIALS

Body	**Technopolymer**
Turbine	**Technopolymer**

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.