

## AP 30L 24V ELECTRIC PUMP



CARBUSET<sup>TM</sup>  
POMPE ELETTRICHE AP 30L

### Cod. APL 30L2

Offers 3 meters jumper cables 24 VDC. AP 30L is a centrifugal pump. Suitable for barrel or tank transfer. Can transfer different liquids such as water, anti-freeze, diesel, motor oil. the small size and weight, just 4 kg, allow to use the AP 30L pump in different application like agriculture, automotive, construction company and industry; for an easy, comfortable and safe fluid transferring.

### Safe

AP 30L pump offers a motor with **double insulated body, this makes the pump robust and durable**. Moreover, **double insulation allows water and emulsion transferring in complete safety**. AP 30L pump has IPX4 (protection against splashing water) and CE marking.

Metal parts are made of stainless steel, for an improved durability and corrosion resistance.

### Complete kit

AP 30L pump comes in a **complete kit: ready to use!** Kit is composed of a suction hose with filter, delivery hose, manual dispensing nozzle with volumetric pump and 3 meters jumper cables 24 VDC. Pump offers a built-in drum connection with 2" BSP and M 64x4 thread.

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

## TECHNICAL DATA SHEET

|                       |                                       |
|-----------------------|---------------------------------------|
| Code                  | <b>APL 30L2</b>                       |
| Voltage               | <b>24 V</b>                           |
| Current type          | <b>DC</b>                             |
| Absorbed power        | <b>135 W</b>                          |
| Absorption            | <b>5,6 A</b>                          |
| Insulation category   | <b>III</b>                            |
| Flow rate             | <b>25 l/m - 6,6 gpm</b>               |
| Discharge head        | <b>1 m</b>                            |
| Sound level           | <b>70 dB</b>                          |
| Operating temperature | <b>-10°C + 40°C / 14 °F to 104 °F</b> |

## MATERIALS

|                   |                        |
|-------------------|------------------------|
| Pump              | <b>Acetal</b>          |
| Dispensing nozzle | <b>Acetal</b>          |
| Suction hose      | <b>Rubber</b>          |
| Delivery hose     | <b>Rubber</b>          |
| Metal parts       | <b>Stainless steel</b> |

## EQUIPMENT SUPPLIED

|                                               |
|-----------------------------------------------|
| Pump                                          |
| N° 5 Clamps                                   |
| Suction hose with filter                      |
| Manual dispensing nozzle with volumetric pump |
| Delivery hose                                 |
| Drum connection 2" BSP and M 64x4             |
| 3 meters (10 ft) jumper cables 24 VDC         |

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.