

# STANDARD BLOW GUN WITH ANGLED METAL PIPE



AIRSET STANDARD

## **Cod. STD 30 1002**

Blow gun with angled stainless steel nozzle, designed for professional industrial use. Nozzle construction guarantees resistance to wear; at the same time, stainless steel is resistant to corrosion and chemicals.

## **Historic Product**

AMPLA Airset Standard blow gun has been on the market for 30 years: a reliable product!

## **Two hanging options**

By the trigger or by the specially designed lug. Both surrounding areas are enforced to withstand increased wear

## **Ergonomic**

Airset Standard blow gun is designed to reduce the risk of repetitive strain injuries. Lever offers a variable and precise air flow; also, it is designed to comfortably fit both small and large hands.

## **Airset Standard blow guns are tested individually during production: no leaks!**

Built in 1/4" Female brass thread, for a safe connection with no leaks

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

## TECHNICAL DATA SHEET

|                                             |                             |
|---------------------------------------------|-----------------------------|
| Blowing force (with a 6bar - 90psi inlet)   | <b>2,5 N</b>                |
| Air consumption (with a 6bar - 90psi inlet) | <b>275 l/m - 9.7 scfm</b>   |
| Sound level (with a 6bar - 90psi inlet)     | <b>83 dB(A)</b>             |
| Connection                                  | <b>1/4" BSP</b>             |
| Weight                                      | <b>136 g - 0.30 lbs</b>     |
| Working temperature                         | <b>-10°/70° - 14/158 °F</b> |
| Max. Pressure                               | <b>10 Bar - 145 psi</b>     |
| Nozzle length                               | <b>123 mm - 5"</b>          |

## MATERIALS

|        |                                   |
|--------|-----------------------------------|
| Handle | <b>Acetal</b>                     |
| Thread | <b>Brass</b>                      |
| Valve  | <b>Acetal and stainless steel</b> |
| Body   | <b>Acetal</b>                     |
| Nozzle | <b>Stainless steel</b>            |

## VERSIONS

| Code        | Description              | Connection |
|-------------|--------------------------|------------|
| STD 30 1002 | Airset Standard L130 BSP | 1/4" BSP   |

## REGULATIONS

|                                       |
|---------------------------------------|
| <b>EU 2003/10/CE</b> Max. 85 dB       |
| <b>OSHA 1910.95 (b)</b> Max. 90 dB 8h |

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.