# TUCANO BLOW GUN WITH AIR SHIELD NOZZLE




AIRSET® TUCANO

**Cod. TCN PP 4040**

This blow gun offers an air shield to reduce the risk of eye injuries. The air shield has sufficient pressure to protect the operator from dust and small chips. Nozzle creates a concentrated jet of air which reduces turbulence, enabling a more precise, effective blowing force. Low noise level. Nozzle is made of rugged plastic, resistant to wear. Moreover, offers a scratch-free material to minimize the risk on delicate surfaces.

**Variable airflow trigger**

Tucano adopts a special valve which allows a progressive control of the lever: this reduces the noise level and air consumption. In the progressive mode the operator can adjust the flow with great precision, which is useful in the most jobs. Instead, fully pressing the lever will use all the blowing force

**Ergonomic handle**

Tucano offers a Soft-Touch handle, made of soft ergonomic rubber, for comfort and easy handling. This material reduces the risk of repetitive strain injuries

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

| | |
|---|---|
| Blowing force (with a 6bar - 90psi inlet) | **2,3 N** |
| Air consumption (with a 6bar - 90psi inlet) | **275 l/m - 9.7 scfm** |
| Sound level (with a 6bar - 90psi inlet) | **80 dB(A)** |
| Connection | **1/4" BSP** |
| Weight | **136 g - 0.30 lbs** |
| Working temperature | **-10°/70° - 14/158 °F** |
| Max. Pressure | **16 Bar - 235 psi** |
| Nozzle length | **56 mm - 2"** |

MATERIALS

| | |
|---|---|
| Handle | **Nylon and rubber** |
| Connection | **Brass** |
| Valve | **Acetal and stainless steel** |
| Body | **Nylon** |
| Nozzle | **Nylon** |

VERSIONS

| Code | Description | Connection |
|---|---|---|
| TCN PP 4040 | Airset Tucano Shield BSP | 1/4" BSP |
| TCN PP 4041 | Airset Tucano Shield NPT | 1/4" NPT |

REGULATIONS

| |
|---|
| **EU 2003/10/CE** Max. 85 dB |
| **OSHA 1910.95 (b)** Max. 90 dB 8h |
| **OSHA STD 1-13.1** Max. 2 bar / 30 psi if the tip becomes blocked |

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.