

# STANDARD BLOW GUN WITH RUBBER TIP



AIRSET<sup>®</sup> STANDARD

## Cod. STD TP 1002

Nozzle made of scratchproof rubber to minimize the risk on delicate surfaces. Rubber tip also works as a pressurizer when cleaning pipes or molds, for a more efficient cleaning. Useful when a compact blow gun is preferable to a larger one.

## Historic Product

AMPLA Airset Standard blow gun has been on the market for 30 years: a reliable product!

## Two hanging options

By the trigger or by the specially designed lug. Both surrounding areas are enforced to withstand increased wear

## Ergonomic

Airset Standard blow gun is designed to reduce the risk of repetitive strain injuries. Lever offers a variable and precise air flow; also, it is designed to comfortably fit both small and large hands.

## Airset Standard blow guns are tested individually during production: no leaks!

Built in 1/4" Female brass thread, for a safe connection with no leaks

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

## TECHNICAL DATA SHEET

|                                             |                             |
|---------------------------------------------|-----------------------------|
| Blowing force (with a 6bar - 90psi inlet)   | <b>2,1 N</b>                |
| Air consumption (with a 6bar - 90psi inlet) | <b>200 l/m - 7 scfm</b>     |
| Sound level (with a 6bar - 90psi inlet)     | <b>83 dB(A)</b>             |
| Connection                                  | <b>1/4" BSP</b>             |
| Weight                                      | <b>136 g - 0.30 lbs</b>     |
| Working temperature                         | <b>-10°/70° - 14/158 °F</b> |
| Max. Pressure                               | <b>10 Bar - 145 psi</b>     |
| Nozzle length                               | <b>19 mm - 0.70"</b>        |

## MATERIALS

|        |                                   |
|--------|-----------------------------------|
| Handle | <b>Acetal</b>                     |
| Thread | <b>Brass</b>                      |
| Valve  | <b>Acetal and stainless steel</b> |
| Body   | <b>Acetal</b>                     |
| Nozzle | <b>Rubber</b>                     |

## VERSIONS

| Code        | Description             | Connection |
|-------------|-------------------------|------------|
| STD TP 1002 | Airset Standard Tip BSP | 1/4" BSP   |
| STD TP 1003 | Airset Standard Tip NPT | 1/4" NPT   |

## REGULATIONS

|                                       |
|---------------------------------------|
| <b>EU 2003/10/CE</b> Max. 85 dB       |
| <b>OSHA 1910.95 (b)</b> Max. 90 dB 8h |

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.