

Tucano blow gun with air shield nozzle and air plug



AIRSET® TUCANO

Code TCN PP 4040E74

Tucano Blow Shield blow gun, featuring a pre-mounted **European DN 7.4** quick air plug for connection to a **quick connector**. The slots on the nozzle create a protective air shield to prevent blown chips from reaching the operator.

Speed

The distinctive feature of the Tucano blow gun with quick air plug is its ability to **quickly connect** to air compressors through specially designed fittings. This air plug allows operators to **easily connect and disconnect the gun**, reducing setup times and improving overall **efficiency**.

Safety

When using compressed air, leaks most often occur at fittings or air plugs. It is therefore essential to ensure **high-quality** connections; this ensures both **cost and energy savings**. Tucano blow guns with quick air plugs guarantee long-lasting quality and airtight connections.

Ergonomics

Ergonomics is another crucial aspect of the Tucano blow gun with quick air plug; it features a soft-touch rubber handle designed to maximize operator **comfort** during extended use. This helps **reduce fatigue** and increase **workplace safety**.

Blow guns with quick air plugs are a **reliable and effective solution** for a wide range of **industrial applications**.

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

Blowing Force (at 6 bar inlet)	2.3 N
Air Consumption (at 6 bar inlet)	275l/m / 9.7 scfm
Noise Level (at 6 bar inlet)	80 dB(A)
Connection	European Profile DN 7.4
Weight	136 g / 0.30 lbs
Working temperature	-10°C/70°C / 14/158 °F
Max. Pressure	16 Bar / 235 psi
Nozzle length	123 mm / 5"

MATERIALS

Handle	Nylon and Rubber
Thread	Brass
Air Plug	Steel with Anti-Corrosion Treatment
Valve	Acetal and Stainless Steel
Body	Nylon
Nozzle	Nylon

VERSIONS

Code	Description	Connection
TCN PP 4040EU74	Airset Tucano Blow Shield EU	European Profile DN 7.4

REGULATIONS

EU 2003/10/CE Max. 85 dB
OSHA Conforme alle normative OSHA

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.