Tucano blow gun with plastic nozzle and air plug

AIRSET® TUCANO

Cod. TCN PL 4040E74

Tucano Blow Gun with an **air plug** already mounted, **European Profile DN 7.4**, for connection to a **quick-release coupling**. The nozzle creates a concentrated airflow, minimizes turbulence, and provides precise and effective blowing. The nozzle is made of durable, wear-resistant plastic; additionally, the plastic material is scratch-resistant for more sensitive surfaces.

Speed

The distinctive feature of the Tucano blow gun with an air plug is its ability to **quickly connect** to air compressors through specially designed couplings. This coupling allows operators to **easily connect and disconnect the gun**, reducing setup times and improving overall **efficiency** of operations.

Safety

When using compressed air, leaks occur more frequently at a fitting or coupling. Therefore, it is crucial to ensure that the **quality** of the connection is perfect; this guarantees **economic and energy savings**. Tucano blow guns with quick couplings can ensure a high-quality and long-lasting seal for your connection.

Ergonomics

Ergonomics is another crucial aspect of the Tucano blow gun with air plug with a soft-touch rubber handle designed to maximize the **comfort** of the operator during prolonged use. This helps to **reduce fatigue** and increase **workplace safety**.

Blow guns with air plugs represent an **effective and reliable solution** for a wide range of **industrial applications**.

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

Blowing Force (at 6 bar inlet)	**2.1 N**
Air Consumption (at 6 bar inlet)	**200 l/m / 7 scfm**
Noise Level (at 6 bar inlet)	**83 dB(A)**
Connection	**European Profile DN 7.4**
Weight	**136 g / 0.30 lbs**
Working temperature	**-10°C/70°C / 14/158 °F**
Max. Pressure	**16 Bar / 235 psi**
Nozzle length	**123 mm / 5”**

MATERIALS

Handle	**Nylon and Rubber**
Thread	**Brass**
Air Plug	**Steel with Anti-Corrosion Treatment**
Valve	**Acetal and Stainless Steel**
Body	**Nylon**
Nozzle	**Nylon**

VERSIONS

Code	Description	Connection
TCN PL 4040EU74	Airset Tucano Blow EU	European Profile DN 7.4

REGULATIONS

EU 2003/10/CE Max. 85 dB

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.