

TUCANO BLOW GUN WITH SAFETY NOZZLE



AIRSET® TUCANO

Cod. TCN S3 4040

Offers a vented rubber nozzle, which creates a wide and efficient flow. Nozzle is silenced for a low noise level. Its rubber tip is designed for delicate surfaces or parts. This special safety nozzle is fixed on an angled stainless steel pipe, for narrow, hard-to-reach spaces; also, keep a safety distance from blown surfaces. The vented tip also prevents pressure exceeding 30 PSI (2 Bar) if the tip becomes blocked (conforms with OSHA Std 1-13.1).

Variable airflow trigger

Tucano adopts a special valve which allows a progressive control of the lever: this reduces the noise level and air consumption. In the progressive mode the operator can adjust the flow with great precision, which is useful in the most jobs. Instead, fully pressing the lever will use all the blowing force

Ergonomic handle

Tucano offers a Soft-Touch handle, made of soft ergonomic rubber, for comfort and easy handling. This material reduces the risk of repetitive strain injuries

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

Blowing force (with a 6bar - 90psi inlet)	2,3 N
Air consumption (with a 6bar - 90psi inlet)	275 l/m - 9.7 scfm
Sound level (with a 6bar - 90psi inlet)	80 dB(A)
Connection	1/4" BSP
Weight	136 g - 0.30 lbs
Working temperature	-10°/70° - 14/158 °F
Max. Pressure	16 Bar - 235 psi
Nozzle length	152 mm - 6"

MATERIALS

Handle	Nylon and rubber
Connection	Brass
Valve	Acetal and stainless steel
Body	Nylon
Nozzle	Rubber
Pipe	Stainless steel

VERSIONS

Code	Description	Connection
TCN S3 4040	Airset Tucano L130 S BSP	1/4" BSP
TCN S3 4041	Airset Tucano L130 S NPT	1/4" NPT

REGULATIONS

OSHA STD 1-13.1 Max. 2 bar / 30 psi if the tip becomes blocked
SUVA PRO
OSHA 1910.95 (b) Max. 90 dB 8h
EU 2003/10/CE Max. 85 dB

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.