

# AP 40L 110V ELECTRIC PUMP WITH ANTI SIPHON VALVE - FOR ADBLUE®/DEF



CARBUSET™  
POMPE ELETTRICHE AP 40L

## Cod. APL 40DB3

Designed for AdBlue®/DEF transferring applications like 200 l, 1000 l drums. AP 40L electric pump offers a built-in anti-siphon valve. 2 meters power cables with Type A plug (USA) 110 VAC. AP 40L is a centrifugal pump.

## Anti-siphon system

AP 40L adopts a valve which is designed to **prevent siphoning of liquid from an aboveground drum to the delivery hose installed at a lower level.**

## Safe

AP 40L pump offers a **motor with double insulated body, this makes the pump robust and durable.** AP 40L pump has IPX4 (protection against splashing water) and CE marking.

## Meets the ISO 22241 standard

## Complete kit

AP 40L pump comes in a **complete kit: ready to use!** Kit is composed of a telescopic suction tube with filter (adjustable from 330 to 970 mm high), delivery hose, manual dispensing nozzle and 2 meters power cables with 2 meters Type A plug (USA) 110 VAC. Pump offers a built-in drum connection with 2" BSP.

## Features

- Pump offers a 2" BSP connection
- **Can be easily installed or removed thanks to a quick coupling system**
- Pump can be rotated in 10 different positions
- Side handle works as a cable storage
- Nozzle hanger: keeps hose within reach and off the floor
- **Available with AL 100 digital flow meter**

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

**TECHNICAL DATA SHEET**

Code	<b>APL 40DB3</b>
Voltage	<b>110 V</b>
Frequency	<b>60 Hz</b>
Current type	<b>AC</b>
Absorbed power	<b>320 W</b>
Absorption	<b>2,9 A</b>
Insulation category	<b>II</b>
Flow rate	<b>40 l/m - 10,5 gpm</b>
Discharge head	<b>1 m</b>
Sound level	<b>70 dB</b>
Operating temperature	<b>-10°C + 40°C / 14 °F to 104 °F</b>

**MATERIALS**

Pump	<b>Polypropylene</b>
Dispensing nozzle	<b>Polypropylene</b>
Telescopic suction tube	<b>Polypropylene</b>
Delivery hose	<b>Rubber</b>
Metal parts	<b>Stainless steel</b>

**EQUIPMENT SUPPLIED**

Pump
N° 2 Clamps
Telescopic suction tube with filter
Manual dispensing nozzle
2,5 m (8 ft) Delivery hose
Drum connection 2" BSP
2 m (6 ft) power cables with Type A plug (USA) 110 VAC

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

## VERSIONS

Code	Description
APL 40DB3	Pump AP 40L AdBlue®110v
APL 40DB350	Pump AP 40L AdBlue® 110v + Flow meter AL 100

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.