

AP 40L 110V ELECTRIC PUMP WITH ANTI SIPHON VALVE - FOR ADBLUE®/DEF



CARBUSET™
POMPE ELETTRICHE AP 40L

Cod. APL 40DB3

Designed for AdBlue®/DEF transferring applications like 200 l, 1000 l drums. AP 40L electric pump offers a built-in anti-siphon valve. 2 meters power cables with Type A plug (USA) 110 VAC. AP 40L is a centrifugal pump.

Anti-siphon system

AP 40L adopts a valve which is designed to **prevent siphoning of liquid from an aboveground drum to the delivery hose installed at a lower level.**

Safe

AP 40L pump offers a **motor with double insulated body, this makes the pump robust and durable.** AP 40L pump has IPX4 (protection against splashing water) and CE marking.

Meets the ISO 22241 standard

Complete kit

AP 40L pump comes in a **complete kit: ready to use!** Kit is composed of a telescopic suction tube with filter (adjustable from 330 to 970 mm high), delivery hose, manual dispensing nozzle and 2 meters power cables with 2 meters Type A plug (USA) 110 VAC. Pump offers a built-in drum connection with 2" BSP.

Features

- Pump offers a 2" BSP connection
- **Can be easily installed or removed thanks to a quick coupling system**
- Pump can be rotated in 10 different positions
- Side handle works as a cable storage
- Nozzle hanger: keeps hose within reach and off the floor
- **Available with AL 100 digital flow meter**

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

| | |
|-----------------------|---------------------------------------|
| Code | APL 40DB3 |
| Voltage | 110 V |
| Frequency | 60 Hz |
| Current type | AC |
| Absorbed power | 320 W |
| Absorption | 2,9 A |
| Insulation category | II |
| Flow rate | 40 l/m - 10,5 gpm |
| Discharge head | 1 m |
| Sound level | 70 dB |
| Operating temperature | -10°C + 40°C / 14 °F to 104 °F |

MATERIALS

| | |
|-------------------------|------------------------|
| Pump | Acetal |
| Dispensing nozzle | Polyamide |
| Telescopic suction tube | Polypropylene |
| Delivery hose | Rubber |
| Metal parts | Stainless steel |

EQUIPMENT SUPPLIED

| |
|--|
| Pump |
| N° 2 Clamps |
| Telescopic suction tube with filter |
| Manual dispensing nozzle |
| 2,5 m (8 ft) Delivery hose |
| Drum connection 2" BSP |
| 2 m (6 ft) power cables with Type A plug (USA) 110 VAC |

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

VERSIONS

| Code | Description |
|-------------|--|
| APL 40DB3 | Pump AP 40L AdBlue®110v |
| APL 40DB350 | Pump AP 40L AdBlue® 110v + Flow meter AL 100 |

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.