AP 40L 230V ELECTRIC PUMP WITH ANTI SIPHON VALVE - FOR ADBLUE®/DEF

CARBUSET
POMPE ELETTRICHE AP 40L

Cod. APL 40DB

Designed for AdBlue®/DEF transferring applications like 200 l, 1000 l drums. AP 40L electric pump offers a built-in anti-siphon valve. 2 meters power cables with Shuko plug 230 VAC. AP 40L is a centrifugal pump.

Anti-siphon system

AP 40L adopts a valve which is designed to **prevent siphoning of liquid from an aboveground drum to the delivery hose installed at a lower level.**

Safe

AP 40L pump offers a **motor with double insulated body, this makes the pump robust and durable**. AP 40L pump has IPX4 (protection against splashing water) and CE marking.

Meets the ISO 22241 standard

Complete kit

AP 40L pump comes in a **complete kit: ready to use!** Kit is composed of a telescopic suction tube with filter (adjustable from 330 to 970 mm high), delivery hose, manual dispensing nozzle, **nozzle can fill all AdBlue® standard tanks**, and 2 meters power cables with Shuko plug 230 VAC. Pump offers a built-in drum connection with 2" BSP.

Features

- Pump offers a 2” BSP connection
- **Can be easily installed or removed thanks to a quick coupling system**
- Pump can be rotated in 10 different positions
- Side handle works as a cable storage
- Nozzle hanger: keeps hose within reach and off the floor
- **Available with AL 100 digital flow meter**

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

TECHNICAL DATA SHEET

Code	**APL 40DB**
Voltage	**230 V**
Frequency	**50/60 Hz**
Current type	**AC**
Absorbed power	**224 W**
Absorption	**0,97 A**
Insulation category	**II**
Flow rate	**40 l/m - 10,5 gpm**
Discharge head	**1 m**
Sound level	**70 dB**
Operating temperature	**-10°C + 40°C / 14 °F to 104 °F**

MATERIALS

Pump	**Acetal**
Dispensing nozzle	**Polyamide**
Telescopic suction tube	**Polypropylene**
Delivery hose	**Rubber**
Metal parts	**Stainless steel**

EQUIPMENT SUPPLIED

Pump
N° 2 Clamps
Telescopic suction tube with filter
Manual dispensing nozzle
2,5 m (8 ft) Delivery hose
Drum connection 2" BSP
2 m (6 ft) power cables with Shuko plug 230 VAC

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

VERSIONS

Code	Description
APL 40DB	Pump AP 40DB AdBlue® 230v
APL 40DB50	Pump AP 40DB AdBlue® 230v + Flow meter AL 100

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.