

## STANDARD BLOW GUN WITH SAFETY NOZZLE



AIRSET STANDARD

### **Cod. STD S3 1002**

Offers a vented rubber nozzle, which creates a wide and efficient flow. Nozzle is silenced for a low noise level. Its rubber tip is designed for delicate surfaces or parts. This special safety nozzle is fixed on an angled stainless steel pipe, for narrow, hard-to-reach spaces; also, keep a safety distance from blown surfaces. The vented tip also prevents pressure exceeding 30 PSI (2 Bar) if the tip becomes blocked (conforms with OSHA Std 1-13.1).

### **Historic Product**

AMPLA Airset Standard blow gun has been on the market for 30 years: a reliable product!

### **Two hanging options**

By the trigger or by the specially designed lug. Both surrounding areas are enforced to withstand increased wear

### **Ergonomic**

Airset Standard blow gun is designed to reduce the risk of repetitive strain injuries. Lever offers a variable and precise air flow; also, it is designed to comfortably fit both small and large hands.

### **Airset Standard blow guns are tested individually during production: no leaks!**

Built in ¼" Female brass thread, for a safe connection with no leaks

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

**TECHNICAL DATA SHEET**

Blowing force (with a 6bar - 90psi inlet)	<b>2,3 N</b>
Air consumption (with a 6bar - 90psi inlet)	<b>275 l/m - 9.7 scfm</b>
Sound level (with a 6bar - 90psi inlet)	<b>80 dB(A)</b>
Connection	<b>1/4" BSP</b>
Weight	<b>136 g - 0.30 lbs</b>
Working temperature	<b>-10°/70° - 14/158 °F</b>
Max. Pressure	<b>10 Bar - 145 psi</b>
Nozzle length	<b>137 mm - 5.40"</b>

**MATERIALS**

Handle	<b>Acetal</b>
Thread	<b>Brass</b>
Valve	<b>Acetal and stainless steel</b>
Body	<b>Acetal</b>
Pipe	<b>Stainless steel</b>
Nozzle	<b>Rubber</b>

**VERSIONS**

<b>Code</b>	<b>Description</b>	<b>Connection</b>
STD S3 1002	Airset Standard L130 S BSP	1/4" BSP
STD S3 1003	Airset Standard L130 S NPT	1/4" NPT

**REGULATIONS**

<b>OSHA 1910.95 (b)</b> Max. 90 dB 8h
<b>OSHA STD 1-13.1</b> Max. 2 bar / 30 psi if the tip becomes blocked
<b>EU 2003/10/CE</b> Max. 85 dB

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.