

# AP 50 LEVER ACTION BARREL PUMP – FOR GASOLINE



CARBUSET

## Cod. APM 50 EXC

The **AP 50 transfer pump** is a **manual piston drum pump** designed for safe and controlled transfer operations. It is particularly suitable in situations where it is necessary to **transfer gasoline, type E5 E10, from 200-liter drums to smaller containers or directly into tanks**, especially in environments where flammable vapors may be present and the use of electrical equipment is not allowed.

The main applications of the AP 50 pump include **auto and truck repair workshops**, the **agricultural sector, construction sites, industry**, and more generally, all **industrial and maintenance environments** where safe manual transfer directly from a drum is required.

Thanks to its manual operation, the AP 50 pump provides a reliable solution for professional applications in **explosion-risk areas (ATEX)** and in operational contexts where safety is a priority.

## Features

- Made of polyamide, a strong and durable material
- Telescopic suction tube adjustable to three different lengths (330, 500, 970 mm)
- The pump is a **ready-to-use kit**, including pump body, suction tube with filter, 2 meters of delivery hose with nozzle, 1.5 m grounding cable with clamp
- Includes a short spout for quick refills of jerrycans or pitchers
- Equipped with a holder for storing the delivery hose after use
- Transport handle and wall mounting bracket included
- Self-priming: Ready to use! No need to prime before operation
- 2" BSP drum connection

## Safe Transfer

The pump is made with materials compatible with the liquids being transferred. A high-quality, durable product with no leaks or breakages. Quality transfer: the liquid is not contaminated.

All metal parts are made of stainless steel for increased durability and corrosion resistance.

## ATEX Certified

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

Allows transfer in potentially explosive environments. The pump carries the marking **CE EX II 2G Ex h IIA T6 Gb. Suitable for installation in Zone 1 and 2 Gas areas.**

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.

**TECHNICAL DATA SHEET**

Code	<b>APM 50 EXC</b>
Amount per stroke	<b>0.5 l</b>
Drum connection	<b>2" BSP</b>
Operating temperature	<b>-10°C + 40°C / 14 °F to 104 °F</b>

**MATERIALS**

Pump	<b>Polyamide</b>
Seals	<b>FKM</b>
Telescopic tube	<b>Polyamide</b>
Delivery hose	<b>Rubber</b>
Nozzle	<b>Polyamide</b>
Metal parts	<b>Stainless steel</b>

**EQUIPMENT SUPPLIED**

Pump
Telescopic suction hose
2 m (7 ft) delivery hose
Nozzle
Delivery hose coupler
Short angled nozzle
N° 2 clamps
1.5 m (5 ft) grounding cable with clamp

Attenzione : il produttore si riserva il diritto di modificare le caratteristiche del prodotto in qualsiasi momento e senza preavviso.